



## 0522VIB1101

### MANAGED PDU

### SPECIFICATIONS

#### Summary:

- vertical PDU (0 U)
- single phase 16 A
- metered input
- metered outlets, switched outlets
- 18 outlets

DIMENSIONS	L x W x D = 1030 x 65 x 52.5 mm (0U) (excl. strain relief, mounting & cable bending radius)
ENCLOSURE	Profile color black, aluminium with stainless steel covers (IP20)
MOUNT	Toolless mount buttons (brackets not included) (distance=800, positions=115, 915mm) 
POWER INPUT	single phase 16 A, 230VAC - 50/60Hz
CABLE ENTRY	power entry side-cover top
CABLE & PLUG	Power lead (3G2,5 halogenfree) with CEE plug 3,0m (strain relief height 2,5cm) 
CONNECTIVITY	databus: 2 x RJ45   Ethernet: RJ45   sensorport: RJ12   USB
INPUT METERING	volt, ampere, kWh, power factor
SWITCHED OUTLETS	18 times bistable close to zero crossing switching relays
METERED OUTLETS	18 times volt, ampere, kWh, power factor
FUSES	n/a
DISPLAY	LCD display with backlight and configurable orientation
OUTLETS	12 x IEC 60320 C13 , 6 x IEC 60320 C19