SCHLEIFENBAUER
LIVING FOR THE POWER TO DELIVER

GM ED23DIP1301

INLINE METER 5.0 GATEWAY

Sommaire de l'offre

- double horizontal PDU
- single phase 32 A
- metered input
- inline
- 1 outlets

SPÉCIFICATIONS

GENERAL	Remote display using smartphone NFC app, up to 100 PDUs share one IP address, ESD safe, toolless hot swappable communications module
CONNECTIVITY	Gateway Module: dual 1Gbps Ethernet (RJ45/USB), RJ45 daisy chain, USB expansion/sensor • TLS encrypted communication to complimentary Enertree PDU monitoring & management software
ENCLOSURE	Profile color black, aluminium with stainless steel covers (IP20)
DIMENSIONS	L x W x D = 209 x 65 x 105 mm (1.5 U) (excl. strain relief, mounting & cable bending radius)
MOUNT	sidecover 19 inch double deep housing
POWER INPUT	single phase 32 A, 230VAC - 50Hz
CABLE ENTRY	power entry rear-side left
CABLE & PLUG	Power lead (3G6 halogenfree) with CEE plug 2,0m (strain relief height 2,5cm)
INPUT METERING	voltage (V), current (A), active power (W), apparent power (VA), reactive power (VAR), energy (kWh), apparent energy (VAh), frequency (Hz), power factor, crest factor, total harmonic distortion (%)
OUTLETS	1 x Exit lead (3G6 halogenfree) with IEC60309 socket 0,5m
FUSES	n/a