





4AF7VMB3366

MANAGED PDU

SPECIFICATIONS

Summary:

- vertical PDU (0 U)
- three phase 32 A
- metered branches (6x)
- metered outlets, switched outlets
- 36 outlets

DIMENSIONS	L x W x D = 1835 x 65 x 52.5 mm (0U) (excl. strain relief, mounting & cable bending radius)	
ENCLOSURE	Profile color black, aluminium with stainless steel covers (IP20)	
MOUNT	Toolless mount buttons (brackets not included) (distance=1333, positions=251, 1584mm)	
POWER INPUT	three phase 32 A, 230/400V - 50/60Hz	
CABLE ENTRY	power entry side-cover top	
CABLE & PLUG	Power lead (5G6 halogenfree) with CEE plug 3,0m (strain relief height 2,5cm)	
CONNECTIVITY	databus: 2 x RJ45 Ethernet: RJ45 sensorport: RJ12 USB	
BRANCH METERING	6 x volt, ampere, kWh, power factor	
SWITCHED OUTLETS	36 times bistable close to zero crossing switching relays	
METERED OUTLETS	36 times volt, ampere, kWh, power factor	
FUSES	6 x Thermal breaker 16A (ETA)	
DISPLAY	LCD display with backlight and configurable orientation	
OUTLETS	30 x IEC 60320 C13 , 6 x IEC 60320 C19	