



**SCHLEIFENBAUER**  
LIVING FOR THE POWER TO DELIVER




## 815AVIP1301

INLINE METER

### SPECIFICATIONS

#### Summary:

- vertical PDU (0 U)
- single phase 32 A
- metered input
- inline
- 1 outlets

|                |  |
|----------------|--|
| DIMENSIONS     | L x W x D = 280 x 65 x 52.5 mm (0U)<br>(excl. strain relief, mounting & cable bending radius)  |
| ENCLOSURE      | Profile color black, aluminium with stainless steel covers<br>(IP20)   |
| MOUNT          | sidecover table mount  |
| POWER INPUT    | single phase 32 A, 230VAC - 50/60Hz  |
| CABLE ENTRY    | power entry side-cover top   |
| CABLE & PLUG   | Power lead (3G6 halogenfree) with CEE plug 2,0m (strain relief height 2,5cm)  |
| CONNECTIVITY   | databus: 2 x RJ45   Ethernet: RJ45   sensorport: RJ12   USB  |
| INPUT METERING | volt, ampere, kWh, power factor  |
| FUSES          | n/a  |
| DISPLAY        | LCD display with backlight and configurable orientation  |
| OUTLETS        | 1 x Exit lead (3G6 halogenfree) with IEC60309 socket<br>0,5m   |

