



SCHLEIFENBAUER
LIVING FOR THE POWER TO DELIVER



86D1VIS3361

SWITCHED PDU

SPECIFICATIONS

Summary:

- vertical PDU (0 U)
- three phase 32 A
- metered input
- switched outlets
- 30 outlets

DIMENSIONS	L x W x D = 1745 x 65 x 52.5 mm (0U) (excl. strain relief, mounting & cable bending radius)
ENCLOSURE	Profile color black, aluminium with stainless steel covers (IP20)
MOUNT	Toolless mount buttons (brackets not included) (distance=1333, positions=206, 1539mm) <div data-bbox="1353 815 1474 936" data-label="Image"> </div>
POWER INPUT	three phase 32 A, 230/400V - 50/60Hz
CABLE ENTRY	power entry side-cover top
CABLE & PLUG	Power lead (5G6 halogenfree) with CEE plug 3,0m (strain relief height 2,5cm) <div data-bbox="1362 1093 1469 1155" data-label="Image"> </div>
CONNECTIVITY	databus: 2 x RJ45 Ethernet: RJ45 sensorport: RJ12 USB
INPUT METERING	volt, ampere, kWh, power factor
SWITCHED OUTLETS	30 times bistable close to zero crossing switching relays
FUSES	6 x Thermal breaker 16A (ETA)
DISPLAY	LCD display with backlight and configurable orientation
OUTLETS	24 x IEC 60320 C13 , 6 x IEC 60320 C19

