

SENSOR

For PDU and DPM3

SUMMARY

Temperature and humidity
Combi Sensor

Digital Sensor with high accuracy

Easy connection to PDU and
DPM3



TEMPERATURE AND HUMIDITY SENSOR

INTERFACE	OneWire
TEMP. OPERATING RANGE	-40°C - 125°C
RH OPERATING RANGE	0 - 100% RH
RH RESPONSE TIME	8 sec.
T RESPONSE TIME	5 sec.
RH ACCURACY (RANGE)	± 2% typical ±3% max (20 - 80% RH)
RH LONG TERM DRIFT	< 0,25% per year
T ACCURACY LIMITS (RANGE)	± 0,3°C
T LONG TERM DRIFT	< 0,02°C per year
PRE CALIBRATED	Yes
PART NR.	T/H combi sensor 123750

© Copyright 2017, Schleifenbauer Products BV. All rights reserved. Unauthorized use and/or duplication of this material without express and written permission from Schleifenbauer Products BV is not allowed. Information contained in this data sheet is up-to-date and correct as at the date of issue. As Schleifenbauer Products cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. To the maximum extent permitted by law, Schleifenbauer Products will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. No express or implied warranties are given other than those implied mandatory by law.