SCHLEIFENBAUER PDU 5.0
Your PDU® *Request form*

Submit a tender text or use this form to specify your PDU request and send it to **sales@schleifenbauer.eu**

Infra

PDU orientation	[ ] Vertical 0U [ ] Horizontal 19"
Phase	[ ] Single-phase 1P [ ] Three-Phase 3P
Current rating	[ ] 10A [ ] 16A [ ] 32A [ ] 63A

Intelligence

Basic PDU non-metered	[ ] Yes [ ] No
Input energy metering	[ ] Yes [ ] No
Branch-level energy metering	[ ] Yes [ ] No
Outlet-level energy metering	[ ] Yes [ ] No
Remote outlet switching	[ ] Yes [ ] No

Communication Module

Gateway Module Choose this module for advanced energy management with the included EnerTree Platform DCEM software. EnerTree offers comprehensive monitoring, risk management, historical analysis, and seamless DCIM integration. By externalising PDU intelligence, it maximises computing power, scalability, and software-driven capacity—eliminating the need for costly internal PDU hardware. Supports up to 10,000 PDUs in system. Measurement refresh rate: once a second.	[ ] Yes [ ] No
Controller Module Choose this module for a standalone PDU solution with a built-in web interface, offering a familiar and conventional approach to PDU management. Ideal for data centres that prefer independent PDU control without relying on an external software platform. The EnerTree Lite embedded software provides a direct, user-friendly interface within the module itself, fully compatible with any existing DCIM software. Supports up to 100 PDUs in system. Measurement refresh rate: once per 5 seconds.	[ ] Yes [ ] No

Options

Outlet type	[ ] Lockable CX Combi outlet [ ] Lockable C13 [ ] Standard C13 [ ] Lockable C19 [ ] Standard C19 [ ] CEE 7/3 (Schuko) [ ] CEE 7/5 (UTE) [ ] BS 1363
Outlet quantity (Specify quantity per outlet type)	
Cable length cable in cm (Standard 3-meter, custom lengths available. Specify in commence)	[ ] Standard 3 Meter [ ] Custom length
Connector plug (standard CEE IEC60309) Options per PDU type: **1P 16A PDU;** IEC60309 1P, CEE 7/4 Schuko, BS 1363, C14 Chassis, C20 chassis **1P 32A PDU;** IEC60309 1P **3P 16A PDU;** IEC60309 3P **3P 32A PDU;** IEC60309 3P **3P 63A PDU;** IEC60309 3P	[ ] CEE 1P [ ] CEE 3P [ ] CEE 7/4 Schuko [ ] BS 1363 [ ] C14 chassis [ ] C20 chassis
Cable entry (standard side cover top)	[ ] Side cover top [ ] Side cover bottom [ ] Front top [ ] Front bottom [ ] Rear
Housing colour	[ ] Black [ ] Red [ ] Blue [ ] Yellow [ ] Orange [ ] Green [ ] Silver
PDU Length	[ ] Standard [ ] Specific length
Dehn overvoltage protector Type 3	[ ] Yes [ ] No
Residual current sensor	[ ] Yes [ ] No
Extra external earthing provision on PDU	[ ] Yes [ ] No
Mounting options	[ ] Toolless Mount [ ] Table Mount [ ] Custom Bracket
Separate temperature humidity sensor	[ ] Yes [ ] No

PDU quantities	
Additional Notes / Custom Requests:	